

N-BUTANOL

**Page:** 1

Compilation date: 03/06/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name: N-BUTANOL CAS number: 71-36-3 EINECS number: 200-751-6 Index number: 603-004-00-6 Product code: GPS9004 Synonyms: BUTYL ALCOHOL

1-BUTANOL

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Manufacture of substances. Laboratory chemicals.

# 1.3. Details of the supplier of the safety data sheet

Section 2: Hazards identification

Select School Supplies The Old Granary Berghill House Oswestry SY11 4PD 01691 770366 sales@selectschoolsupplies.co.uk



2.1. Classification of the subst	ance or mixture
Classification under CLP:	Flam. Liq. 3: H226; Acute Tox. 4: H302; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3:
	H335; STOT SE 3: H336
Most important adverse effects:	Flammable liquid and vapour. Harmful if swallowed. Causes skin irritation. Causes
	serious eye damage. May cause respiratory irritation. May cause drowsiness or
	dizziness.

N-BUTANOL

Page: 2

2.2. Label elements	
Label elements under CLP:	
	H226: Flammable liquid and vapour.
וומבמות שנמושווישיווש.	H226. Flammable liquid and vapour. H302: Harmful if swallowed.
	H315: Causes skin irritation.
	H318: Causes serious eye damage.
	H335: May cause respiratory irritation.
Signal words:	H336: May cause drowsiness or dizziness.
	-
Hazard pictograms:	GHS02: Flame GHS05: Corrosion
	GHS05: Corrosion GHS07: Exclamation mark
Precautionary statements:	P261: Avoid breathing.
	P280: Wear.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
2.3. Other hazards	
Other hazards:	This substance/mixture contains no components considered to be either persistent,
	bioaccumulative and
	toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
PBT:	This product is not identified as a PBT/vPvB substance.
Section 3: Composition/inform	nation on ingredients
3.1. Substances	
Chemical identity:	
CAS number:	71-36-3
EINECS number:	200-751-6
Contains:	Molecular Formula: C4H10O

Molecular Weight: 74.12 g/mol.

# Section 4: First aid measures

## 4.1. Description of first aid measures

Skin contact: Remove contaminated clothing immediately and wash skin with soap and water. Get

medical attention if any discomfort continues. Consult a doctor.

Eye contact: Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses

and open eyes wide apart. Get medical attenton immediately. Continue to rinse.

N-BUTANOL

		age: 3
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse	
	mouth with water. Consult a doctor.	
Inhalation:	If breathed in, move person into fresh air. If not breathing, give artificial respiration.	
	Consult a doctor.	
4.2. Most important symptoms	and effects, both acute and delayed	
Skin contact:	May be harmful if absorbed through the skin. There may be irritation and redness at the	
	site of contact.	
Eye contact:	Causes serious eye irritation There may be pain and redness. The eyes may water	
	profusely. The vision may become blurred. May cause permanent damage. May cause	
	permanent blindness.	
Ingestion:	May be harmful if swallowed. There may be soreness and redness of the mouth and	
	throat. There may be difficulty swallowing. There may be vomiting. Nausea and stomach	
	pain may occur.	
Inhalation:	May be harmful if inhaled. May cause respiratory tract irritation. There may be irritation of	
	the throat with a feeling of tightness in the chest. Exposure may cause coughing or	
	wheezing. May cause drowsiness and dizziness.	
4.3. Indication of any immediat	e medical attention and special treatment needed	
Immediate / special treatment:	Show this safety data sheet to the doctor in attendance. Eye bathing equipment should	
	be available on the premises.	
	be available on the premises.	

## Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Water spray. Alcohol resistant foam. Dry chemical powder. Carbon dioxide.

## 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Carbon oxides. Flash back possible over considerable distance

## 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. In case of fire, evacuate area. Fight fire remotely due to the risk of explosion. Use water spray to cool unopened containers.

## Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8. Page: 3

N-BUTANOL

Page: 4

					Fay	. 4	
6.2. Envi	ronmental precaution	s					
Enviro	nmental precautions:	Spillages o	or uncontroled discharges int	o watercourses must be IMM	IEDIATELY alerted to		
		the Enviro	nmental Agency or other app	ropriate regulatory body. Pre	event further leakage		
		or spillage	if safe to do so. Do not let pr	oduct enter drains. Discharg	je into environment		
		must be av	voided.				
6.3. Meth	ods and material for o	containmen	t and cleaning up				
(	Clean-up procedures:	Contain sp	pillage, and then collect with a	an electrically protected vacu	um cleaner or by		
		wet-brushi	ng and place in container for	disposal according to local	regulations.		
6.4. Refe	rence to other section	IS					
Referer	nce to other sections:	For persor	nal protection, see section 8.	For waste disposal, see sec	tion 13.		
ection 7:	Handling and stora	ge					
7.1. Prec	autions for safe hand	ling					
На	Indling requirements:	Avoid dire	ct contact with the substance	. Avoid contact with skin and	eves. Avoid inhalation		
-	3 - 11 - 11		Avoid direct contact with the substance. Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to				
		•	e build up of electrostatic cha		-		
7.2. Cond	ditions for safe storag	•	g any incompatibilities				
			ool place. Keep container tigh	the algood is a dry and wall y	contilated place		
	Storage conditions.		s which are opened must be				
			lygroscopic - Handle and sto	re under men gas. Storage c	ass (TRGS 510).		
		Flammable	e liquids.				
7.3. Spec	cific end use(s)						
	Specific end use(s):	No other s	pecific uses stipulated other	than the uses mentioned in s	section 1.2.		
ection 8:	Exposure controls/	personal p	protection				
8.1. Cont	trol parameters						
Workp	lace exposure limits:			Respirable dust			
	ate 8 hour T	-W/A	15 min. STEL	8 hour TWA	15 min. STEL	]	
	K	-	50 ppm (154 mg/m3)	-	-		
0	· · · · · · · · · · · · · · · · · · ·					]	

## 8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

## 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Handle in accordance with good

industrial hygiene and safety practice. Wash hands before and after breaks and at the end of workday.

N-BUTANOL

Respiratory protection:Where risk assessment shows air-purifying respirators are appropriate use a full-face<br/>respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator<br/>cartridges as a backup to engineering controls. If the respirator is the sole means of<br/>protection, use a full-face supplied air<br/>respirator. Use respirators and components tested and approved under appropriate<br/>government standards such as NIOSH (US) or CEN (EU).

- Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with application laws and good laboratory practises. Wash and dry hands. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. For full contact use Nitrile rubber gloves with a minimum thickness layer of 0.4mm, and a break through time of 480 mins. For splash contact use Nitrile rubber gloves with a minimum thickness layer of 0.2mm, and a break through time of 72 mins. If used in solution, or mixed with substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves.
  - **Eye protection:** Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU).
- Skin protection: Complete suit protecting against chemicals. Flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
  Environmental: Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Discharge into the environment must be avoided.

#### Section 9: Physical and chemical properties

9.1. Information on basic physi	cal and chemical properties		
State:	Liquid		
Colour:	Colourless		
Solubility in water:	Soluble		
Boiling point/range °C:	116-118 Melting	point/range °C:	-90
Flammability limits %: lower:	1.4	upper:	11.2
Flash point °C:	35 Va	pour pressure:	5 hPa at 20C
Relative density:	0.81		
9.2. Other information			

**Other information:** Relative vapour density - 2.56 (Air = 1.0)

Page: 5

N-BUTANOL

#### Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under recommended storage conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Exposure to moisture. Heat, flames and sparks

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Alkali metals. Bases. Strong acids. Halogens.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes. In the event of fire: see section 5

### Section 11: Toxicological information

## 11.1. Information on toxicological effects

#### **Toxicity values:**

Route	Species	Test	Value	Units
ORAL	RAT	LD50	790	mg/kg
INHALATION	RAT	4H LC50	8,000	ppm
DERMAL	RABBIT	LD50	3,400	mg/kg

### Relevant hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	ING	Based on test data
Skin corrosion/irritation	DRM	Based on test data
Serious eye damage/irritation	OPT	Based on test data
STOT-single exposure	INH	Based on test data

#### Symptoms / routes of exposure

**Skin contact:** May be harmful if absorbed through the skin. There may be irritation and redness at the site of contact.

- **Eye contact:** Causes serious eye irritation There may be pain and redness. The eyes may water profusely. The vision may become blurred. May cause permanent damage. May cause permanent blindness.
  - Ingestion: May be harmful if swallowed. There may be soreness and redness of the mouth and

Page: 6

N-BUTANOL

Page: 7

throat. There may be difficulty swallowing. There may be vomiting. Nausea and stomach pain may occur.Inhalation: May be harmful if inhaled. May cause respiratory tract irritation. There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or

wheezing. May cause drowsiness and dizziness. **Other information:** RTECS: EO1400000 Drying, cracking of the skin, skin irritation. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

### Section 12: Ecological information

### 12.1. Toxicity

#### **Ecotoxicity values:**

Species	Test	Value	Units
Pimephales promelas (Fathead minnow)	96H LC50	1,840	mg/l
Daphnia magna (Water flea)	48H EC50	1,983	mg/l

#### 12.2. Persistence and degradability

Persistence and degradability: No data available.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation - Oncorhynchus mykiss (rainbow trout) - 24h - 921 mg/l.

Bioconcentration factor (BCF): 0.38.

### 12.4. Mobility in soil

Mobility: Soluble in water.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Other adverse effects: No data available.

### Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra

care in igniting as this material is highly flammable. Offer surplus and non-recycable

solutions to a licensed disposal company.

Disposal of packaging: Dispose of as unused product.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

N-BUTANOL

	N-BOTANOL		
	P	age:	8
Section 14: Transport informat	ion		
14.1. UN number			
UN number:	UN1120		
14.2. UN proper shipping name			
Shipping name:	BUTANOLS		
14.3. Transport hazard class(es			
Transport class:	3		
14.4. Packing group			
Packing group:	III		
14.5. Environmental hazards			
Environmentally hazardous:	No Marine pollutant: No		_
14.6. Special precautions for us	Ser		
Tunnel code:	D/E		
Transport category:	3		
Section 15: Regulatory information	ation		
15.1. Safety, health and enviror	mental regulations/legislation specific for the substance or mixture		]
-	This safety datasheet complies with the requirements of Regulation (EC) No.		
opecine regulations.	1907/2006.		
15.2. Chemical Safety Assessm	ent		
Chemical safety assessment:	For this product a chemical safety assessment was not carried out.		
Section 16: Other information			
Other information			
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No		_
	453/2010.		
	* indicates text in the SDS which has changed since the last revision.		
Phrases used in s.2 and 3:	H226: Flammable liquid and vapour.		
	H302: Harmful if swallowed.		
	H315: Causes skin irritation.		
	H318: Causes serious eye damage.		
	H335: May cause respiratory irritation.		
	H336: May cause drowsiness or dizziness.		
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive		
	and shall be used only as a guide. This company shall not be held liable for any		
	damage resulting from handling or from contact with the above product.		