INDUSTRIAL METHYLATED SPIRIT 70%

Page: 1

Compilation date: 12/10/2018

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: INDUSTRIAL METHYLATED SPIRIT 70%

CAS number: 64-17-5
EINECS number: 200-578-6
Product code: GPS9018

Synonyms: ABSOLUTE ALCOHOL

NON-DENATURED ETHANOL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC21: Laboratory chemicals.

1.3. Details of the supplier of the safety data sheet

Select School Supplies The Old Granary Berghill House Oswestry SY11 4PD 01691 770366



sales@selectschoolsupplies.co.uk

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225; Eye Irrit. 2: H319

Classification under CHIP: F: R11

Most important adverse effects: Highly flammable liquid and vapour. Causes serious eye irritation.

2.2. Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





INDUSTRIAL METHYLATED SPIRIT 70%

Precautionary statements: P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical advice/attention.

P403+235: Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Other hazards: This substance/mixture contains no components considered to be either persistent,

bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at

levels of 0.1% or higher.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: INDUSTRIAL METHYLATED SPIRIT 70%

CAS number: 64-17-5 **EINECS number:** 200-578-6

Contains: Molecular Formula: C2H6O

Molecular weight: 46.07 g/mol

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor. Never give

anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If unconscious, check for

breathing and apply artificial respiration if necessary. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: No data available.Inhalation: No data available.

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: No data available.

Section 5: Fire-fighting measures

Page: 2

INDUSTRIAL METHYLATED SPIRIT 70%

Page: 3

5.1. Extinguishing media

Extinguishing media: Water spray. Alcohol resistant foam. Dry chemical powder. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Not applicable.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of

ignition. Evacuate the area immediately. Ensure adequate ventilation. Avoid breathing

vapours, mist or gas. Use personal protective equipment. Beware of vapours

accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Contain spillage, and then collect with an electrically protected vacuum cleaner or by

wet-brushing and place in container for disposal according to local regulations (see

section 13).

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up

of electrostatic charge.

For precautions see section 2.2.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Containers which are

opened must be carefully resealed and kept upright to prevent leakage. Hygroscopic.

Suitable packaging: Not applicable.

7.3. Specific end use(s)

Specific end use(s): No special requirement.

Section 8: Exposure controls/personal protection

INDUSTRIAL METHYLATED SPIRIT 70%

Page: 4

8.1. Control parameters

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	1,920 mg/m3	-	-	-

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands

before breaks and at the end of workday.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves. Nitrile gloves. Rubber gloves. Breakthrough time of the glove material

> 1 hour.

Eye protection: Face-shield. Safety glasses.

Skin protection: Impervious clothing. Flame retardant antistatic protective clothing. The type of protective

equipment must be selected according to the concentration and amount of the

dangerous substance at the specific workplace.

Environmental: Do not let product enter drains. Prevent from entering in public sewers or the immediate

environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Solubility in water: Soluble

Boiling point/range°C: 78 Melting point/range°C: -114

Flammability limits %: lower: 3.3 upper: 19

Flash point°C: 14 Part.coeff. n-octanol/water: log Pow: -0.349

Autoflammability°C: 363 Vapour pressure: 59.5 hPa

Relative density: 0.789 g/mL

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: No data available.

INDUSTRIAL METHYLATED SPIRIT 70%

Page: 5

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: No data available.

10.4. Conditions to avoid

Conditions to avoid: Heat. Flames. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Alkali metals. Oxidising agents. Peroxides.

10.6. Hazardous decomposition products

Haz. decomp. products: Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORAL	RAT	LD50	10,470	mg/kg
GASES	RAT	4H LC50	124.7	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Based on test data

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: No data available.
Inhalation: No data available.
Delayed / immediate effects: No data available.

ayour minioulate enfects. No data available

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

INDUSTRIAL METHYLATED SPIRIT 70%

Page: 6

Ecotoxicity values:

Species	Test	Value	Units
Ceriodaphnia dubia	96H LC50	5,012	mg/l
FISH	96H LC50	15.3	mg/l
ALGAE	48H EC50	275	mg/l

12.2. Persistence and degradability

Persistence and degradability: Rapidly biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra

care in igniting as this material is highly flammable. Offer surplus and non-recyclable

solutions to a licensed disposal company.

Recovery operations: Not applicable.

Disposal of packaging: Dispose of as unused product.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1170

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: 2

INDUSTRIAL METHYLATED SPIRIT 70%

Page: 7

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: This safety datasheet complies with the requirements of Regulation (EC) No.

1907/2006.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

R11: Highly flammable.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.