PETROLEUM ETHER 40-60

Page: 1

Compilation date: 18/10/2018

Revision No: 1

## Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: PETROLEUM ETHER 40-60

CAS number: 8032-32-4 **EINECS number: 232-453-7** Product code: GPS9037

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC21: Laboratory chemicals.

### 1.3. Details of the supplier of the safety data sheet

Select School Supplies The Old Granary Berghill House Oswestry SY11 4PD 01691 770366



sales@selectschoolsupplies.co.uk

## Section 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 1: H224; Aquatic Chronic 2: H411; Skin Irrit. 2: H315; STOT SE 3: H336; Asp.

Tox. 1: H304

Classification under CHIP: T: R45; T: R46; Xn: R65; F+: R12; Xi: R38; N: R51/53

Most important adverse effects: Extremely flammable liquid and vapour. May be fatal if swallowed and enters airways.

Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long

lasting effects.

### 2.2. Label elements

### Label elements under CLP:

Hazard statements: H224: Extremely flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

#### PETROLEUM ETHER 40-60

Page: 2

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS08: Health hazard GHS09: Environmental









**Precautionary statements:** P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331: Do NOT induce vomiting.

P370+378: In case of fire: Use dry powder or dry sand for extinction.

P403: Store in a well-ventilated place.

P235: Keep cool.

### 2.3. Other hazards

Other hazards: This substance/mixture contains no components considered to be either persistent,

bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at

levels of 0.1% or higher.

PBT: This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

## 3.1. Substances

Chemical identity: PETROLEUM ETHER 40-60

**CAS number:** 8032-32-4 **EINECS number:** 232-453-7

Contains: Petroleum ether <= 100%

## Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Wash

out mouth with water. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If unconscious, check for

breathing and apply artificial respiration if necessary. Consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** No symptoms. **Ingestion:** No data available.

PETROLEUM ETHER 40-60

Page: 3

Inhalation: No data available.

Delayed / immediate effects: May cause drowsiness or dizziness.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: No data available.

## Section 5: Fire-fighting measures

## 5.1. Extinguishing media

Extinguishing media: Dry sand. Dry chemical powder. Do NOT use water jet.

### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Not applicable.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Use water spray to cool unopened containers.

#### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure

adequate ventilation. Beware of vapours accumulating to form explosive concentrations.

Vapours can accumulate in low areas. Eliminate all sources of ignition. Evacuate the

area immediately. Refer to section 8 of SDS for personal protection details.

## 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand,

earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

## Section 7: Handling and storage

## 7.1. Precautions for safe handling

Handling requirements: Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from

sources of ignition - No smoking. Take measures to prevent the build up of electrostatic

charge.

For precautions see section 2.2.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Containers which are

opened must be carefully resealed and kept upright to prevent leakage.

PETROLEUM ETHER 40-60

Page: 4

Suitable packaging: Not applicable.

7.3. Specific end use(s)

Specific end use(s): No special requirement.

## Section 8: Exposure controls/personal protection

## 8.1. Control parameters

Workplace exposure limits: No data available.

#### 8.1. DNEL/PNEC Values

**DNEL / PNEC** No data available.

#### 8.2. Exposure controls

Engineering measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands

before breaks and at the end of workday.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 480 min Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.2 mm

Break through time: 30 min

Eye protection: Face-shield. Safety glasses.

**Skin protection:** Complete suit protecting against chemicals. Flame retardant antistatic protective

clothing. The type of protective equipment must be selected according to the

concentration and amount of the dangerous substance at the specific workplace.

**Environmental:** Do not let product enter drains. Prevent from entering in public sewers or the immediate

environment.

## Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Boiling point/range°C: 30-60 Flammability limits %: lower: 1

upper: 7 Flash point°C: -49

Autoflammability°C: 245

# 9.2. Other information

Other information: No data available.

PETROLEUM ETHER 40-60

Page: 5

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: No data available.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: No data available.

### 10.4. Conditions to avoid

Conditions to avoid: Heat. Flames. Sources of ignition.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

### 10.6. Hazardous decomposition products

Haz. decomp. products: Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

## **Section 11: Toxicological information**

## 11.1. Information on toxicological effects

# **Toxicity values:**

Route	Species	Test	Value	Units
ORAL	RAT	LD50	2,000	mg/kg
INHALATION	RAT	4H LC50	25.3	mg/l
DERMAL	RBT	LD50	3,350	mg/kg

# Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Based on test data
STOT-single exposure	-	Based on test data
Aspiration hazard	-	Based on test data

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

Eye contact: No symptoms.Ingestion: No data available.Inhalation: No data available.

Delayed / immediate effects: May cause drowsiness or dizziness.

Other information: Not applicable.

PETROLEUM ETHER 40-60

Page: 6

### **Section 12: Ecological information**

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Very toxic to aquatic organisms.

### Section 13: Disposal considerations

## 13.1. Waste treatment methods

Disposal operations: Offer surplus and non-recyclable solutions to a licensed disposal company. Waste

material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No

mixing with other waste. Handle uncleaned containers like the product itself.

Recovery operations: Not applicable.

Disposal of packaging: Dispose of as unused product.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

### 14.1. UN number

UN number: UN1268

## 14.2. UN proper shipping name

Shipping name: ADR/RID: PETROLEUM DISTILLATES, N.O.S.

IMDG: PETROLEUM DISTILLATES, N.O.S.

IATA: Petroleum distillates, n.o.s.

# 14.3. Transport hazard class(es)

Transport class: 3

#### PETROLEUM ETHER 40-60

Page: 7

### 14.4. Packing group

Packing group: 2

### 14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

### 14.6. Special precautions for user

Special precautions: No special precautions.

## Section 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: This safety datasheet complies with the requirements of Regulation (EC) No.

1907/2006.

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

## **Section 16: Other information**

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H224: Extremely flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

R12: Extremely flammable.

R38: Irritating to skin.

R45: May cause cancer.

R46: May cause heritable genetic damage.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65: Harmful: may cause lung damage if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.